

WAP Series

WAP1010



10.1" Fanless Stainless Windows Touch Panel PC




WIFI



Bluetooth



TPM2.0



DDR4



IP65



Fanless



M12 Connector



Wide Voltage



- 10.1-inch Windows Touch Panel PC with Intel® Celeron® J6412 Processor
- Projective Capacitive Touch Screen Full Flat Design
- Stainless Steel Housing with Front IP65/ Rear IP54 Design
- 1 x LAN, 2 x USB, 1 x COM by M12 Connector with waterproof cover and chain
- Flexible installation with wall, stand, and VESA mounting options
- Wide-ranged voltage DC In 12V-24V



Food
Processing



Pharmaceutical
Manufacturing



Cleanroom
Application



Chemical
Environment



Animal Feed
Production

Specification

WAP1010

Display

| | |
|----------------|---------------------------------------------------|
| Display Type | 10.1" WXGA 16:10 LCD |
| Resolution | 1280 x 800 |
| Brightness | 500 nits |
| Contrast Ratio | 800 |
| Viewing Angle | -89° ~ 89° (H) ; -89° ~ 89° (V) |
| Response Time | 29 ms |
| Touch Type | 10 Points Projective Capacitive Multi-Touchscreen |

System

| | |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CPU | Intel® Celeron® J6412 Processor (1.5M Cache, up to 2.60 GHz) |
| GPU | Intel® UHD Graphics |
| Memory | 1 x 260-pin DDR4 3200MHz SO-DIMM Socket, 8GB, Up to 32GB Max. |
| Storage | 128GB SSD (Optional 256GB/512GB/1TB) |
| OS Support | Windows 10/11, Ubuntu LTS |
| LAN Controller | 2 x Intel® I210AT (Co-lay I210IT/I211AT) Gigabit Ethernet |
| Wireless | WiFi with waterproof Antenna (Optional) BT (Optional) |
| TPM | TPM 2.0 |
| Watchdog Timer | H/W Reset, 1sec. ~ 65535sec and 1sec. or 1min./step |
| H/W Monitor | Monitoring CPU & System Temperature and Voltage |
| Expansion | 1 x M.2 Type E 2230 supports WiFi module (PCIe x1 & USB 2.0 Signal) 1 x M.2 Type B 3042/2242 support WWAN+GNSS or SSD (SATA and USB 3.0/USB 2.0 signal) 1 x M.2 Type M supports 2260 slot |
| IO Ports | 2 x USB 2.0 with waterproof cover and chain 2 x M12 4-pin(D-coded female) for LAN with waterproof cover and chain 1 x M12 8-pin (male) COM1(RS-232) with waterproof cover and chain 1 x M12 DC-In Connector 1 x Power Switch on the back |

Physical

| | |
|-------------------|-----------------------------------------------------------------------------------------------------------------|
| Construction | Front: Sheet metal, SECC + black painting, matt finish Rear: Sheet metal, SECC + black painting, matt finish |
| CPU Cooler (Type) | Fanless heatsink |
| Mounting | Wall / Stand / VESA 100mm x 100mm |
| Power Mode | ATX |
| Power Connector | M12 Connector |
| Power Input | DC 12-24V |
| Power Adapter | DC 24V/2.5A, 60W |

Packing List

| | |
|--------------------|---------------------------------------------------------|
| Standard Accessory | 1 x Power Adapter (24V/2.5A) Waterproof M12 DC Cable |
| Product Dimension | 295.4 x 213.4 X48 mm |
| Product Weight | 3.5Kg |

Environment

| | |
|-----------------------|----------------------------|
| IP Rating | Front IP65 / Rear IP54 |
| Certification | CE / FCC Class A |
| Operating Temperature | 0°C ~ 40°C (32°F ~ 104°F) |
| Storage Temperature | 0°C ~ 60°C (32°F ~ 140°F) |
| Relative humidity | 10% to 85%, non condensing |

Overview

Unit : mm

