

WCP Series

# WCP1167



11.6" Commercial Premium Windows Touch Panel PC



- 11.6" Windows System
- Intel Alder Lake Processor
- Fanless & Front Panel IP65
- Rich & Flexible I/O Port Design
- Aluminum Die Casting Housing
- Magnetic I/O Port Cover For Easy Maintaining



Amusement and Entertainment Device



KIOSK



Self-service Terminal



Interactive Digital Signage



Gambling Machine

## Specification

## WCP1167

## Display

|               |                                      |
|---------------|--------------------------------------|
| Display Type  | 11.6" TFT LCD                        |
| Resolution    | 1920 x 1080                          |
| Aspect Ratio  | 16:9                                 |
| Brightness    | 450 Nits                             |
| Touch Panel   | 10 Points Projected Capacitive Touch |
| Viewing Angle | -89° ~ 89°(H) ; -89° ~ 89°(V)        |

## Main System

|                  |   |
|------------------|---|
| Processor        | Intel® Core™ i5-1245UE vPro Deca Core<br>Intel® Core™ i7-1265UE vPro Deca Core (Optional)<br>Intel® Core™ i3-1215UE Hexa Core (Optional)<br>Intel® Celeron® 7305E Penta Core (Optional)   |
| GPU              | Intel® Iris® Xe   |
| Memory           | 1 x SO-DIMM, DDR5 8GB, 4800MHz (Max.32GB)<br>1 x SO-DIMM, DDR5, 4800MHz (Max.32GB)  |
| Storage          | 1 x M.2 2280 Slot, B-Key 256GB (Max.1TB)  |
| I/O Ports        | 4 x USB 3.0<br>1 x COM (RS232)<br>1 x COM (RS232/422/485)-(RS232 support 5V/12V)<br>2 x LAN (1 x Intel® I211, 1 x Intel® I219LM)<br>1 x HDMI 2.0<br>1 x DVI-I<br>1 x 3.5mm phone jack Mic-in<br>1 x 3.5mm phone jack Line-out<br>1 x MB support 9-36V DC-in |
| Operating System | Windows 10 IoT, Windows 10 Pro, Windows 11, Linux   |

## Physical

|                    |   |
|--------------------|---|
| Camera             | Front Camera : 2.0 MP                                 |
| Audio              | 2 x 2W Speaker  |
| Mounting           | VESA Mount 100 x 100 mm                               |
| Color              | Black / White   |
| Dimensions (WxHxD) | 295.8 x 189.6 x 34.9 mm                               |
| Weight             | TBA   |
| Enclosure          | Aluminum Die Casting                                  |
| Cooling System     | Fanless   |
| Button             | 1 x Power On/Off                                      |
| Power Adapter      | DC 19V/4.74A, 90W                                     |
| Security           | Wake-on-LAN<br>TPM 2.0<br>Intel vPro<br>PXE           |
| Standard Accessory | 1 x Medical Grade Power Adapter<br>4 x Rubber Stopper |

## Environment

|                       |                                    |
|-----------------------|------------------------------------|
| IP Rating             | Front IP65                         |
| Certification         | CE, FCC Class A, CB, cTUVus, EU RF |
| Operating Temperature | 0°C ~ 40°C                         |
| Storage Temperature   | -20°C ~ 60°C                       |
| Relative Humidity     | 20% ~ 80% (non-condensing)         |
| Warranty              | 2 Years                            |

## Overview

