

WMP Series

WMP1167



11.6" Medical Premium Windows Touch Panel PC



Fanless



Front IP65



- 11.6" Windows System
- Intel Alder Lake Processor
- IEC60601 Medical Certified
- Aluminum Die Casting Housing
- Rich & Flexible I/O Port Design
- Magnetic I/O Port Cover For Easy Maintaining



Radiology



Surgical



Medical Cart



Bedside Terminal



Mobile X-Ray

Specification

WMP1167

Display

Display Type	11.6" TFT LCD
Resolution	1920 x 1080
Aspect Ratio	16:9
Brightness	450 Nits
Touch Panel	10 Points Projected Capacitive Touch
Viewing Angle	-89° ~ 89°(H) ; -89° ~ 89°(V)

Main System

Processor	Intel® Core™ i5-1245UE vPro Deca Core
	Intel® Core™ i7-1265UE vPro Deca Core (Optional)
	Intel® Core™ i3-1215UE Hexa Core (Optional)
	Intel® Celeron® 7305E Penta Core (Optional)
GPU	Intel® Iris® Xe
Memory	2 x SODIMM, DDR5 4800MHz, 8GB (Up to 64GB)
Storage	1 x M.2 2280 Slot, B-Key 256GB (Max.1TB)
I/O Ports	4 x USB 3.0
	1 x COM (RS232)
	1 x COM (RS232/422/485)-(RS232 support 5V/12V)
	2 x LAN (1 x Intel® I211, 1 x Intel® I219LM)
	1 x HDMI 2.0
	1 x DVI-I
	1 x 3.5mm phone jack Mic-in
	1 x 3.5mm phone jack Line-out
	1 x MB support 9-36V DC-in
	1 x POAG (Equipotential)
	Operating System

Physical

Camera	Front Camera : 2.0 MP
Audio	2 x 2W Speaker
Mounting	VESA Mount 100 x 100 mm
Color	Black / White
Dimensions (WxHxD)	295.8 x 189.6 x 34.9 mm
Weight	TBA
Enclosure	Aluminum Die Casting
Cooling System	Fanless
Button	1 x Power On/Off
Power Adapter	DC 19V/4.74A, 90W
Security	Wake-on-LAN
	TPM 2.0
	Intel vPro
	PXE
Standard Accessory	1 x Medical Grade Power Adapter
	4 x Rubber Stopper

Environment

IP Rating	Front IP65
Certification	CE, FCC Class A, CB, cTUVus, EU RF
Operating Temperature	0°C ~ 40°C
Storage Temperature	-20°C ~ 60°C
Relative Humidity	20% ~ 80% (non-condensing)
Warranty	2 Years

Overview

