

WCP Series

WCP1567



15.6" Automation Premium Windows Touch Panel PC



WIFI



Bluetooth



Front IP65



Fanless



- 15.6" Windows System with Intel 15th/13th/12th/8th Core™ Processor
- Fanless Aluminum Die Casting Housing and Black/White Appearance Design
- Magnetic IO Port Cover for Easy Maintenance
- Front Panel IP65 Protection
- Rich & Flexible I/O Port Design
- Wide-range Voltage DC input 9-36V



Amusement and
Entertainment Device



Smart Cities
Terminal



Self-service
Terminal



Industrial



Gambling
Machine

Specification

WCP1567

Display				
Model Name	WCP1567-Whiskey Lake	WCP1567-Alder Lake	WCP1567-Raptor Lake	WCP1567-Arrow Lake
Display Type	15.6" TFT LCD			
Resolution	1920 x 1080			
Aspect Ratio	16:9			
Brightness	350 nits			
Touch Panel	True-Flat 10-Points Projected Capacitive Touch			
Viewing Angle	-89° ~ 89° (H) ; -89° ~ 89° (V)			
Contrast Ratio	1000			

Main System

Model Name	WCP1567-Whiskey Lake	WCP1567-Alder Lake	WCP1567-Raptor Lake	WCP1567-Arrow Lake
Processor	Intel® Core™ i5-8365UE (Optional: i3-8145UE / Celeron® 4305UE, MOQ required)	Intel® Core™ i5-1245UE (Optional: i7-1265UE / i3-1215UE / Celeron® 7305E, MOQ required)	Intel® Core™ i5-1335U (Optional: i7-1355U / i3-1315U, MOQ required)	Intel® Core™ Ultra 5 Processor 235U (Optional: Ultra 7 Processor 265U, MOQ required)
GPU	Intel® UHD Graphics 620 for Core-I Processor Intel® UHD Graphics 610 for Celeron Processor	Intel® Iris® Xe Graphics eligible for Core-i5 & Core-i7 Processor Intel® UHD Graphics for Core i3 & Celeron Processor		Intel® Graphics
NPU	No Support			Intel® AI Boost with 12 TOPS
Memory	1 x SO-DIMM, DDR4 8GB, 2400 MHz (Max.32GB) 1 x SO-DIMM, DDR4, 2400 MHz (Max.32GB)	1 x SO-DIMM, DDR5 8GB, 4800 MHz (Max.32GB) 1 x SO-DIMM, DDR5, 4800 MHz (Max.32GB)	1 x SO-DIMM, DDR5 8GB, Up to 5200 MHz (Max.32GB) 1 x SO-DIMM, DDR5, Up to 5200 MHz (Max.32GB)	1 x SO-DIMM, DDR5 8GB, Up to 6400MHz (Max.32GB) 1 x SO-DIMM, DDR5, Up to 6400MHz (Max.32GB)
Storage	1 x M.2 2280 Slot, 256GB (Max.1TB)			
I/O Ports	4 x USB 3.0 (Type-A) 2 x COM (RS232) 2 x LAN (1 x Intel® I211, 1 x Intel® I219LM)		4x USB 3.2 Gen2 (Type A) 2 x 2.5GbE LAN (1 x Intel® I226-V, 1 x Intel® I226-LM(Support Wake On LAN)) 1 x HDMI 2.0, 4096x2160@60Hz 1 x DVI-I 1 x Mic-in 1 x Line-out 1 x Power Jack support 9~36V DC-in 1 x Power On/Off Button 1 x Tactical switch for Power On/Off	
				1 x HDMI 2.1,7680 ×4320@60Hz
			1 x HDMI 2.0	
Communication	WLAN : IEEE 802.11a/b/g/n/ac; 2.4GHz/5GHz (Internal Antenna) Bluetooth 4.2			
Operating System	Windows 10 IoT LTSC, Windows 11, Linux			

Physical

Camera	Front Camera : 2.0 MP
Audio	2 x 2W Speaker
Mounting	VESA Mount 100 x 100 mm
Color	Black / White
Enclosure	Aluminum Die Casting
Cooling System	Fanless
Power Adapter	DC 19V/4.74A, 90W
TPM	TPM 2.0

Packing List

Dimensions (WxDxH)	394.3 x 256.2 x 54.4 mm
Weight	4.6 Kg
Box Dimension	50 x 16 x 42 cm
Box Weight	6.1 Kg
Standard Accessory	1 x 90W Power Adapter
	4 x Rubber Stopper

Environment

IP Rating	Front IP65
Certification	CE, FCC Class A, EU RF
Operating Temperature	0° C ~ 40° C (32° F ~ 104° F)
Storage Temperature	-20° C ~ 60° C (-4° F ~ 140° F)
Relative Humidity	20% ~ 80% (non-condensing)
Warranty	2 Years

Overview



Tactical Switch

